

IN THE CLAIMS:

The status of each claim that has been introduced in the above-referenced application is identified in the ensuing listing of the claims. This listing of the claims replaces all previously submitted claims listings.

1. (Currently amended) A method for calibrating a programmable material consolidation apparatus, comprising:
viewing ~~at least one location substantially at a consolidation elevation of a fabrication site of the~~
programmable material consolidation apparatus at least one location substantially at a consolidation elevation of the fabrication site, from a location above the consolidation elevation, and while moving a viewpoint from which viewing is effected along a path of a plurality of spaced apart reference pixels, each having a common, known dimension;
evaluating data obtained from viewing the at least one location; and
determining an amount of adjustment to be made to at least one component of the programmable material consolidation apparatus, in response to the act of evaluating.
2. (Canceled)
3. (Original) The method of claim 1, wherein viewing is effected substantially at the consolidation elevation.
4. (Original) The method of claim 1, wherein evaluating comprises comparing the data to at least one expected data value.
5. (Original) The method of claim 1, wherein determining comprises determining that no adjustment of the at least one component need be made.
6. (Original) The method of claim 1, further comprising:
adjusting the at least one component by the amount of adjustment.

7. (Previously presented) The method of claim 1, further comprising:
adjusting the at least one component of the programmable material consolidation apparatus by at least a portion of the amount of adjustment.

8. (Original) The method of claim 1, further comprising:
fabricating at least one feature substantially at the consolidation elevation.

9. (Original) The method of claim 8, wherein viewing comprises viewing the at least one feature.

10. (Original) The method of claim 9, wherein fabricating includes fabricating a plurality of reference pixels substantially at the consolidation elevation.

11. (Original) The method of claim 10, wherein evaluating data comprises comparing actual locations of the plurality of reference pixels to anticipated locations for the plurality of reference pixels.

12. (Original) The method of claim 11, further comprising:
adjusting reference grid data by at least a portion of the amount of adjustment.

13. (Original) The method of claim 11, further comprising:
adjusting a material consolidation element of the programmable material consolidation apparatus by at least a portion of the amount of adjustment.

14. (Original) The method of claim 13, further comprising:
adjusting reference grid data by at least a portion of the amount of adjustment.

15. (Canceled)

16. (Currently amended) The method of claim ~~15~~1, further comprising:
positioning a calibration plate including the plurality of spaced apart reference pixels
substantially at the consolidation elevation.
17. (Currently amended) The method of claim ~~15~~1, wherein moving is effected
substantially linearly.
18. (Currently amended) The method of claim ~~15~~1, wherein viewing further
comprises detecting transitions in contrast.
19. (Currently amended) The method of claim ~~15~~1, wherein viewing further
comprises determining a number of reference pixels viewed as the viewpoint is moved a
particular distance.
20. (Original) The method of claim 19, wherein evaluating data comprises evaluating
the particular distance, the number of reference pixels viewed, and the common, known
dimension of the reference pixels to determine a magnification at the viewpoint.
21. (Original) The method of claim 20, further comprising:
repeating the acts of moving, viewing, and evaluating at least once to verify the magnification at
the viewpoint.
22. (Original) The method of claim 20, further comprising:
using the magnification at the viewpoint to control operation of a material consolidation element
of the programmable material consolidation apparatus.

23. (Previously presented) The method of claim 1, further comprising:
directing selectively consolidating energy toward a plurality of locations of the consolidation elevation.

24. (Previously presented) The method of claim 23, wherein directing includes directing the selectively consolidating energy toward at least one location proximate a corner or an edge of a rectangular field of exposure at the consolidation elevation.

25. (Original) The method of claim 23, wherein at least some of the plurality of locations are in substantially linear alignment.

26. (Previously presented) The method of claim 23, wherein viewing comprises viewing actual locations of the consolidation elevation to which the selectively consolidating energy is directed.

27. (Previously presented) The method of claim 26, further comprising:
placing at least one light-sensitive element substantially at the consolidation elevation, the viewing being effected with the at least one light-sensitive element.

28. (Canceled)

29. (Previously presented) The method of claim 26, wherein evaluating data comprises comparing the actual locations to anticipated locations of the consolidation elevation where selectively consolidating energy was expected to be directed.

30. (Previously presented) The method of claim 23, further comprising:
adjusting a material consolidation element of the programmable material consolidation apparatus
by at least a portion of the adjustment amount to increase a linearity of a path of
consolidating energy generated by the material consolidation element.

31-37 (Canceled)